C 1 3453 SEQUENC		STATE OF MARYLAND WELL COMPLETION REPORT	THIS REPORT MUST BE SUBMITTED WITHIN 45 DAYS AFTER WELL IS COMPLETED.
(HIS NUMBER IS TO BE PUNCHED IN COLS. 3-6 ON ALL CARDS)		FILL IN THIS FORM COMPLETELY PLEASE TYPE	COUNTY
ST/CO USE ONLY DATE WELL DATE Received	COMPL	ETED Depth of Well	PERMIT NO.
6 13 15	121	22 26 20 (TO NEAREST FOOT) (	11/23/15 SC 28 29 30 31 32 33 34 35 36 37
OWNER_COTTON			
STREET OR RFD 19 5 SUBDIVISION	vat 1	TATUNS SECTION TOWN	LOT
WELL LOG		GROUTING RECORD Yes no	[C 3]
Not required for driven wells		WELL HAS BEEN GROUTED (Circle Appropriate Box)  V 44	1 2 PUMPING TEST
STATE THE KIND OF FORMATIONS PENETRATED, COLOR, DEPTH, THICKNESS AND IF WATER BEA	RING	TYPE OF GROUTING MATERIAL (Circle one)  CEMENT CM BENTONITE CLAY B C	HOURS PUMPED (nearest hour)
DESCRIPTION (Use additional sheets if needed) FROM TO	check if water bearing	NO. OF BAGS 46 NO. OF POUNDS 45 48	PUMPING RATE (gal. per min.)
Hard Tangray 0 30		GALLONS OF WATER 50	METHOD USED TO
Hard gray 30 33		perth of grout SEAL (to nearest foot) from ft. to 54 BOTTOM 58	MEASURE PUMPING RATE
Hard gray Tan 33 40		48 TOP 52 54 BOTTOM 58 (enter 0 if from surface)	WATER LEVEL (distance from land surface)
Hard gray 40 59		casing types insert ST CO	BEFORE PUMPING 17 20 ft.
Med hard Tan 59 53		appropriate STEEL CONCRETE	WHEN PUMPING 22 25 ft.
Hardtan 55 65		below PLASTIC OTHER	TYPE OF PUMP USED (for test)
mod hard Brown 65 70		MAIN Nominal diameter Total depth CASING top (main) casing of main casing	A air P piston T turbine
Hardtan 70 73		TYPE (nearest inch)! (nearest foot)	C centrifugal R rotary (describe below)
M. 1 1 17 13 80	-	60 61 63 64 66 70	J jet S submersible
Med NAVO (WC 100 95		C OTHER CASING (if used) A diameter depth (feet)	27 27
Hara Gray 95 100		H inch from to	DRILLER INSTALLED PUMP YES NO
Med have black 13		S I	(CIRCLE) (YES or NO)
Havd Gray 100 295	النف	G CONTRACTOR	IF DRILLER INSTALLS PUMP, THIS SECTION MUST BE COMPLETED FOR ALL WELLS.
Med hard Gray 295 300	1	screen type or open hole ST BR HO	TYPE OF PUMP INSTALLED PLACE (A,C,J,P,R,S,T,O) 29
Hard Gray 300 313		appropriate STEEL BRASS OPEN BRONZE HOLE	IN BOX 29.  CAPACITY:
Med hard Gray 313 315		code below PL OT OTHER	GALLONS PER MINUTE (to nearest gallon) 31 35
Hard Gray 315 500	3/1		PUMP HORSE POWER 37 41
NUMBER OF UNSUCCESSFUL WELLS:	)	DEPTH (nearest ft.)	PUMP COLUMN LENGTH (nearest ft.)
WELL HYDROFRACTURED yes	N	E 1 8 9 11 15 17 21	CASING HEIGHT (circle appropriate box and enter casing height)
CIRCLE APPROPRIATE LETTER		H 23 24 26 30 32 36	49 LAND SURFACE
A WELL WAS ABANDONED AND SEALED WHEN THIS WELL WAS COMPLETED  F ELECTRIC LOG OBTAINED		S C 3 R 38 39 41 45 47 51	below (nearest) foot)
P TEST WELL CONVERTED TO PRODUCTION WELL		R 38 39 41 45 47 51 E E SLOT SIZE 1 2 3	A LOCATION OF WELL ON LOT
I HEREBY CERTIFY THAT THIS WELL HAS BEEN CONSTR ACCORDANCE WITH COMAR 28.04.04 "WELL CONSTRUCT	ION" AND	DIAMETER (NEAREST	SHOW PERMANENT STRUCTURE SUCH AS BUILDING, SEPTIC TANKS, AND /OR
IN CONFORMANCE WITH ALL CONDITIONS STATED IN THE ABOVE CAPTIONED PERMIT, AND THAT THE INFORMATION PRESENTED HEREIN IS ACCURATE AND COMPLETE TO THE BEST OF MY KNOWLEDGE.		OF SCREEN INCH)	LANDMARKS AND INDICATE NOT LESS THAN TWO DISTANCES
DRILLERS LIC. NO. 11 MM D3 0 4	L .	from to	(MEASUREMENTS TO WELL)
David Lely		GRAVEL PACK  IF WELL DRILLED  WAS FLOWING WELL  WAS FLOWING WELL	The state of the s
DRILLERS SIGNATURE (MUST MATCH SIGNATURE ON APPLICATION)		INSERT F IN BOX 68 68  MDE USE ONLY	Baylan) 1
ub. No. 1 VW D 5 6 4 1		(NOT TO BE FILLED IN BY DRILLER) T (E.R.O.S.) W Q	75
Mat Mottitt		70 72	•
SITE SUPERVISOR (sign. of driller or journeym responsible for sitework if different from permittee		TELESCOPE LOG 74 75 76 CASING INDICATOR OTHER DATA	
DENI/ CDoo		COUNTY	Marie Control of the