

C1 0253		SEQUENCE NO. (MDE USE ONLY)		STATE OF MARYLAND WELL COMPLETION REPORT FILL IN THIS FORM COMPLETELY PLEASE PRINT OR TYPE		THIS REPORT MUST BE SUBMITTED WITHIN 45 DAYS AFTER WELL IS COMPLETED.	
(THIS NUMBER IS TO BE PUNCHED IN COLS. 3-6 ON ALL CARDS)						COUNTY NUMBER <u>ANB 48 836</u>	
ST/CO USE ONLY DATE Received		DATE WELL COMPLETED <u>081996</u>		Depth of Well 22 <u>280</u> 26 (TO NEAREST FOOT)		PERMIT NO. FROM "PERMIT TO DRILL WELL" <u>H0-93-0281</u>	
OWNER <u>Thompson</u>		STREET OR RFD <u>Quarterfield Dr</u>		TOWN <u>Friendship</u>			
SUBDIVISION <u>QUARTERFIELD</u>		SECTION <u>20</u>		LOT <u>20</u>			
WELL LOG Not required for driven wells		GROUTING RECORD WELL HAS BEEN GROUTED (Circle Appropriate Box) <u>Y</u> <u>N</u>		PUMPING TEST HOURS PUMPED (nearest hour) <u>3</u>			
STATE THE KIND OF FORMATIONS PENETRATED, THEIR COLOR, DEPTH, THICKNESS AND IF WATER BEARING		TYPE OF GROUTING MATERIAL (Circle one) CEMENT <u>CM</u> BENTONITE CLAY <u>BC</u>		PUMPING RATE (gal. per min.) <u>20</u>			
DESCRIPTION (Use additional sheets if needed)		NO. OF BAGS <u>15</u> NO. OF POUNDS <u>1410</u>		METHOD USED TO MEASURE PUMPING RATE <u>Bucket</u>			
FEET FROM TO		GALLONS OF WATER <u>90</u>		WATER LEVEL (distance from land surface)			
Sand 0 55		DEPTH OF GROUT SEAL (to nearest foot) from <u>0</u> ft. to <u>52</u> ft.		BEFORE PUMPING <u>50</u> ft.			
Gray Mica 55 280		TOP (enter 0 if from surface)		WHEN PUMPING <u>54</u> ft.			
Rock		CASING RECORD casing types insert appropriate code below		TYPE OF PUMP USED (for test)			
		<u>ST</u> STEEL <u>CO</u> CONCRETE		<u>A</u> air <u>P</u> piston <u>T</u> turbine			
		<u>PL</u> PLASTIC <u>OT</u> OTHER		<u>C</u> centrifugal <u>R</u> rotary <u>O</u> other (describe below)			
		MAIN CASING TYPE		<u>J</u> jet <u>S</u> submersible			
		Nominal diameter top (main) casing (nearest inch) <u>6</u>					
		Total depth of main casing (nearest foot) <u>60</u>					
		OTHER CASING (if used)		PUMP INSTALLED DRILLER WILL INSTALL PUMP (CIRCLE) YES <u>NO</u>			
		diameter inch depth (feet) from to		IF DRILLER INSTALLS PUMP, THIS SECTION MUST BE COMPLETED FOR ALL WELLS.			
		SCREEN RECORD screen type or open hole insert appropriate code below		TYPE OF PUMP INSTALLED PLACE (A,C,J,P,R,S,T,O) IN BOX 29			
		<u>ST</u> STEEL <u>BR</u> BRASS <u>HO</u> OPEN HOLE		CAPACITY: GALLONS PER MINUTE (to nearest gallon)			
		<u>PL</u> PLASTIC <u>OT</u> OTHER		PUMP HORSE POWER			
NUMBER OF UNSUCCESSFUL WELLS: <u>0</u>		WELL HYDROFRACTURED <u>Y</u> <u>N</u>		PUMP COLUMN LENGTH (nearest ft.)			
CIRCLE APPROPRIATE LETTER		C 2		CASING HEIGHT (circle appropriate box and enter casing height)			
A A WELL WAS ABANDONED AND SEALED WHEN THIS WELL WAS COMPLETED		DEPTH (nearest ft.)		<u>+</u> above			
E ELECTRIC LOG OBTAINED		<u>H0</u> <u>58</u> <u>280</u>		<u>-</u> below			
P TEST WELL CONVERTED TO PRODUCTION WELL		SLOT SIZE 1 2 3		LAND SURFACE <u>2</u> (nearest foot)			
I HEREBY CERTIFY THAT THIS WELL HAS BEEN CONSTRUCTED IN ACCORDANCE WITH COMAR 26.04.04 "WELL CONSTRUCTION" AND IN CONFORMANCE WITH ALL CONDITIONS STATED IN THE ABOVE CAPTIONED PERMIT, AND THAT THE INFORMATION PRESENTED HEREIN IS ACCURATE AND COMPLETE TO THE BEST OF MY KNOWLEDGE.		DIAMETER OF SCREEN		LOCATION OF WELL ON LOT SHOW PERMANENT STRUCTURE SUCH AS BUILDING, SEPTIC TANKS, AND /OR LANDMARKS AND INDICATE NOT LESS THAN TWO DISTANCES (MEASUREMENTS TO WELL)			
TYPE: MWD/MSD/MGD		GRAVEL PACK IF WELL DRILLED WAS FLOWING WELL INSERT F IN BOX 68		15' 20' well			
DRILLERS LIC. NO. <u>24</u>		MDE USE ONLY (NOT TO BE FILLED IN BY DRILLER)					
DRILLERS SIGNATURE <u>Joseph E. Mayne</u>		T (E.R.O.S.) W Q					
LIC. NO. <u>27</u>		70 72 74 75 76					
SITE SUPERVISOR (sign. of driller or journeyman responsible for sitework if different from permittee)		TELESCOPE CASING LOG INDICATOR OTHER DATA					