1 -0100	SEQUENCE NO. (MDE USE ONLY)		STATE OF MARYLAND	THIS REPORT MUST BE SUBMITTED WITHIN 45 DAYS AFTER WELL IS COMPLETED.
2 3 6	11403		WELL COMPLETION REPORT FILL IN THIS FORM COMPLETELY	COUNTY
THIS NUMBER IS TO BE PUNCHED N COLS. 3-6 ON ALL CARDS)			PLEASE TYPE	NUMBER
T/CO USE ONLY DATE Received	DATE WELL	COMPL	ETED Depth of Well 2/	PERMIT NO. FROM "PERMIT TO DRILL WELL"
MM DD YY			22 700 ²⁶ 04	PR 28 29 30 31 32 33 34 35 36 37
3 13 15 2			(TO NEAREST FOOT)	2. 25 25 30 01 02 30 37 30 30 30
DWNER BED Last name 1447 WOOTLSTEEF TOWN WOUTLSTEEF				
STREET OR RFD SECTION LOT				
WELL LOG			GROUTING RECORD yes no	C 3
Not required for driven wells			WELL HAS BEEN GROUTED (Circle Appropriate Box)	1 2 PUMPING TEST
STATE THE KIND OF FORMATIONS PENETRATED, THEIR COLOR, DEPTH, THICKNESS AND IF WATER BEARING			TYPE OF GROUTING MATERIAL (Circle one)	HOURS PUMPED (nearest hour)
DESCRIPTION (Use	FEET	check if water	CEMENT C M BENTONITE CLAY B C	8 9
additional sheets if needed)	FROM TO	bearing	NO. OF BAGS NO. OF POUNDS	PUMPING RATE (gal. per min.)
			GALLONS OF WATER	METHOD USED TO MEASURE PUMPING RATE
Daller we			DEPTH OF GROUT SEAL (to nearest foot) from ft. to ft.	
			from ft. to ft. to ft. to ft. to ft. ft. to ft. ft. to ft.	WATER LEVEL (distance from land surface)
cheese Fr	um		casing CASING RECORD	BEFORE PUMPING 7 ft.
Unapart 1	1		types insert ST CO	WHEN PUMPING
240 to 7	00		appropriate code PL OT	22 25
0			below PLASTIC OTHER	TYPE OF PUMP USED (for test) A air P piston T turbine
Granite			MAIN Nominal diameter Total depth	A air P piston T turbine
Granite rock			CASING top (main) casing of main casing TYPE (nearest inch)! (nearest foot)	C centrifugal R rotary O (describe below)
10010			60 61 63 64 66 70	J jet S submersible
			E OTHER CASING (if used) A diameter depth (feet)	27 27
			inch from to	PUMP INSTALLED
			C	DRILLER INSTALLED PUMP (CIRCLE) (YES or NO)
				IF DRILLER INSTALLS PUMP, THIS SECTION
			CORETA RECORD	MUST BE COMPLETED FOR ALL WELLS.
			screen type or open hole STBRHO	TYPE OF PUMP INSTALLED PLACE (A,C,J,P,R,S,T,O) 29
			insert STEEL BRASS OPEN	IN BOX 29. CAPACITY:
		-	appropriate code below BRONZE HOLE	GALLONS PER MINUTE (to nearest gallon) 31 35
			below PLASTIC OTHER	PUMP HORSE POWER
	and the same	Page 1	C 2 DEPTH (nearest ft.)	PUMP COLUMN LENGTH
NUMBER OF UNSUCCESSF	UL WELLS:	0	1 2	(nearest ft.)
WELL HYDROFRACTURED	yes	no N	E 1	CASING HEIGHT (circle appropriate box and enter casing height)
		(N	С,	above LAND SURFACE
A WELL WAS ABANDONED AND SEALED			H 23 24 26 30 32 36 S	(nearest)
WHEN THIS WELL WAS			C 3 R 38 39 41 45 47 51	49 below (not)
P TEST WELL CONVERTED		V	E SLOT SIZE 1 2 3	LOCATION OF WELL ON LOT
I HEREBY CERTIFY THAT THIS WEL ACCORDANCE WITH COMAR 26.04.0			DIAMETER (NEAREST	SHOW PERMANENT STRUCTURE SUCH AS BUILDING, SEPTIC TANKS, AND /OR
IN CONFORMANCE WITH ALL CONDITIONS STATED IN THE ABOVE CAPTIONED PERMIT, AND THAT THE INFORMATION PRESENTED			OF SCREEN INCH)	LANDMARKS AND INDICATE NOT LESS THAN TWO DISTANCES
HEREIN IS ACCURATE AND COMPLETE TO THE BEST OF MY KNOWLEDGE.			from to	(MEASUREMENTS TO WELL)
DRILLERS LIC. NO.1 M SD 009 1			GRAVEL PACK	
ant to			IF WELL DRILLED WAS FLOWING WELL INSERT F IN BOX 68	3075
DRILLERS SIGNATURE (MUST MATCH SIGNATURE ON APPLICATION)			MDE USE ONLY	House
LIC. NO. 1 M _ D 1			(NOT TO BE FILLED IN BY DRILLER) T (E.R.O.S.) W Q	3
				\$ ₩
SITE SUPERVISOR (sign. of driller or journeyman			70 72 74 75 76 TELESCOPE 1.0G	500 8
responsible for sitework if different from permittee)			TELESCOPE LOG CASING INDICATOR OTHER DATA	Sipile 3
DENV-CR97 COUNTY				