Al Mille and in sa

193370 Date argilable 1988/11/4. Printed US/3/182018.

11.28.88

DATE

FOR STORM DRAINAGE SYSTEMS,

AND PUBLIC ROADS, HOWARD COUNTY

APPROVED:

OCHI & ASSOCIATES, INC.


11 1 0 0


SCALE: 1" = 100'

OCTOBER 1988

Current Zoning: R

Sketch Plan S-88-23 Waiver Request WP-88-50





INLET END VIEW SIDE VIEW REQUIRES EFFLUENT FILTER AT OUTLET SEE BAT NOTE 16. TOP VIEW OF TLET END VIEW 2000 T.S W/C


INLET END VIEW - PROVIDE ONE 1/4" VB ON PUMP DISCHARGE LINE. ADJUST PROVIDE 1/4" WEEP HOLE-PROVIDE ONE QUICK HIGH WATER DISCONNECT UNION ON PUMP ALARM=622.05 DISCHARGE LINE WITHIN REACH PUMP ON = 621.65 FROM MANHOLE. PUMP OFF = 621.55 50 GAL, DOSE (MIN.) \* PUMP SOLD SEPARATELY AT ADDITIONAL COST PUMP TO BE A NORWECO HB105 EFFLUENT PUMP ( HP, 115 VOLTS) OR EQUIVALENT SEE DETAIL THIS SHEET **BOT TANK ELEV. = 619.30** 800 gal = 18 TOP VIEW OUTLET END VIEW BABYLON VAULT CO. 2000 T.S


PROPOSED BAT 2,000 GAL. 2 COMPARTMENT PRE-TREATMENT CHAMBER DETAIL

PROPOSED 2,000 GAL. SINGLE COMPARTMENT BAT PRE-TREATMENT PUMP CHAMBER DETAIL

Cord

Capacity gallons per minute





Capacity liters per minute 50 100 150 200

PROPOSED PUMP CHAMBER PUMP DETAIL

Discharge

1-1/2"

**EFFLUENT FILTER DETAIL** 

\* SEE BAT NOTE 16

Hank Oswald 10/22/18

BAT DETAIL

## norveco SERVICE PRO

WASP SERIES INTEGRATED SYSTEM CONTROLS

**●** 

## MODEL HB105 EFFLUENT PUMP WATERTIGHT JUNCTION BOX SUBMERSIBLE EFFLUENT PUMP

TYPICAL PUMP INSTALLATION

U.S. GALLONS PER MINUTE

PUMP PERFORMANCE CURVE

PROPOSED BAT PRE-TREATMENT PUMP DETAIL

WASP SERIES CONTROLS **CONTROL PANEL DETAIL** 

1. THIS SYSTEM REQUIRES TWO CONTROL PANELS TO BE MOUNTED SIDE BY SIDE. ONE CONTROL PANEL WILL CONTROL THE PUMP IN THE BAT PRE-TREATMENT CHAMBER AS WELL AS ONE OF THE TWO AERATORS WITHIN THE BAT UNIT. THE SECOND PANEL WILL CONTROL THE PUMP IN THE TRENCH PUMP CHAMBER AS WELL AS THE SECOND AERATOR WITHIN THE

## **BAT NOTES**

- 1. ANY CHANGE TO THE LOCATIONS OR DEPTHS TO ANY COMPONENTS MUST BE APPROVED BY THE ENGINEER AND THE HOWARD COUNTY HEALTH DEPARTMENT PRIOR TO INSTALLATION. A REVISED SITE PLAN MAY BE REQUIRED. THE MAXIMUM DEPTH OF THE BAT PER THE MANUFACTURER'S SPECIFICATION IS 5 FEET.
- THE BLOWER MAY NOT BE LOCATED MORE THAN 50 FEET FROM THE TANK BASED ON THE MANUFACTURER'S SPECIFICATIONS. 4. THE BAT SYSTEM SHALL BE MAINTAINED AND OPERATED FOR THE LIFE OF THE SYSTEM. 5. THE BAT SHALL BE OPERATED BY AND MAINTAINED BY A CERTIFIED SERVICE PROVIDER. WITHIN ONE MONTH OF INSTALLATION, A PERSON INSTALLING THE BAT SYSTEM SHALL
- REPORT TO THE MARYLAND DEPARTMENT OF THE ENVIRONMENT (MDE) IN A MANNER ACCEPTABLE TO MDE, THE ADDRESS AND DATE OF COMPLETION OF THE BAT INSTALLATION AND THE TYPE OF BAT INSTALLED. 7. ELECTRICAL WORK FOR THE BAT INSTALLATION MUST BE PERFORMED BY A LICENSED
- 8. AN AGREEMENT AND EASEMENT MUST BE COMPLETED AND SIGNED BY ALL APPLICABLE PARTIES, AND RECORDED IN LAND RECORDS OF HOWARD COUNTY.
- CERTIFICATION FROM THE MANUFACTURER PRIOR TO FINAL APPROVAL OF THE 10. DOSE OF THE BAT PRE-TREATMENT PUMP CHAMBER TO BE:

9. THE HEALTH DEPARTMENT REQUIRES DOCUMENTATION FOR THE START-UP

- 50 GALLONS ON A PUMP RUN TIME OF 1.9 MINUTES (1 MIN., 51 SEC.). 11. DOSE OF THE PUMP CHAMBER TO TRENCHES TO BE:
- DEMAND DOSE OF 144 GALLONS 12. BAT PRE-TREATMENT PUMP TO BE A NORWECO HB105 PUMP OR EQUIVALENT. 13. PUMP TO TRENCHES TO BE A MYERS ME3 SERIES PUMP OR EQUIVALENT. 14. BAT PRE-TREATMENT CHAMBER TO BE THE BABYLON VAULT CO. 2000 T.S. TWO
- COMPARTMENT CHAMBER WITH SLOTTED WALL UK EQUIVALENT.

  15. BAT PRE-TREATMENT PUMP CHAMBER TO BE THE BABYLON VAULT CO. 2000 T.S. SINGLE 14. BAT SYSTEM TO BE A NORWECO SINGULAIR MODEL TNT-1000 GPD OR EQUIVALENT.
  - 15. PUMP CHAMBER TO BE THE BABYLON VAULT CO. 2000 T.S. SINGLE COMPARTMENT CHAMBER OR EQUIVALENT. 16. EFFLUENT FILTER MUST BE NSF CERTIFIED AND DESIGNED TO TREAT A MINIMUM OF
  - 18. ALL RISERS TO BE 6" ABOVE FINAL GRADE

			TIVEIN		SIGN	CHART			
TRENCH	GROUND ELEV.	STONE ELEV.	PIPE INV. ELEV.	BOTTOM ELEV.	DEPTH OF STONE	EFFECTIVE DEPTH	TRENCH LENGTH	TRENCH WIDTH	TRENCH
l1	628.4'	625.8'	625.8'	620.4'	5.4'	2.5'	82.3'	3.0'	10.0'
12	627.9'	625.8'	625.8'	619.9'	5.9'	2.5'	82.3'	3.0'	10.0'
13	627.8'	625.8'	625.8'	619.8'	6.0'	2.5	82.3'	3.0'	10.0'

OWNER/DEVELOPER/PETITIONER **ELEONORA DON-MINEVICH** 

3255 ROSCOMMON DRIVE GLENELG, MD 21737

ENGINEERING GROUP, LLC

DRAWN BY: Civil Engineering for Land Development

SHEET#: 2 of 2 ROFESSIONAL CERTIFICATION: I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY ICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND, LICENSE NO. 32025, EXPIRATION DATE: JUNE 20, 2019

SITE PLAN FOR BAT INSTALLATION ROSCOMMON ESTATES LOT 9 3255 ROSCOMMON DRIVE TAX MAP 22 GRID 1 HOWARD COUNTY, MARYLAND

3RD ELECTION DISTRICT Phone: 443.325.5076

1130 Dovedale Court, Suite 200 Marriottsville, Maryland 21104 Fax: 410.696.2022 Email: info@sillengine

CHECKED BY: PS SCALE: AS SHOWN DATE: OCTOBER 12, 2018 PROJECT#: 18-061

DESIGN BY:

PARCEL 549

**EFFLUENT PUMPS** 

ORDERING INFORMATION

ME3F (High Flow)

MYERS® ME3 SERIES

Cycles

17. TDH (TOTAL DYNAMIC HEAD) = STATIC HEAD + DISTAL HEAD + FRICTION HEAD + LATERAL FRICTION HEAD SAFETY FACTOR | 4.81 + 2.0 + 6.62 +1.5 = 14.93, USE 15'

PROPOSED SINGLE COMPARTMENT PUMP CHAMBER DETAIL

