C1 67613 SEQUENCE NO. (MDE USE ONLY)	STATE OF MARYLAND WELL COMPLETION REPORT	THIS REPORT MUST BE SUBMITTED WITHIN 45 DAYS AFTER WELL IS COMPLETED.
(THIS NUMBER IS TO BE PUNCHED IN COLS. 3-6 ON ALL CARDS)	FILL IN THIS FORM COMPLETELY PLEASE TYPE	COUNTY NUMBER
ST/CO USE ONLY DATE Beceived DATE WELL COMPLETED Depth of Well Approved PERMIT NO. FROM "PERMIT TO DRILL WELL" MM 10 10 - 12 1600 26 Approved FROM "PERMIT TO DRILL WELL" 13 13 13 13 12 13 20 10 26 7/30/21 10 - 13 33 34 35 36 37		
WELL SITE ADDRESS leat name 4351 TEN DAKS ROUTER TOWN DAYTON		
SUBDIVISION SECTION LOT		
WELL LOG Not required for driven wells	GROUTING RECORD Yes no WELL HAS BEEN GROUTED Y N	C3
STATE THE KIND OF FORMATIONS PENETRATED, THEIR COLOR, DEPTH, THICKNESS AND IF WATER BEARING	WELL HAS BEEN GROUTED (Circle Appropriate Box) TYPE OF GROUTING MATERIAL (Circle one)	PUMPING TEST
DESCRIPTION (Use FEET check if water additional sheets if needed) FROM TO bearing	CEMENT CIAY BC	HOURS PUMPED (nearest hour)
Deepen	NO. OF BAGS 46 NO. OF POUNDS 45 46 GALLONS OF WATER DEPTH OF GROUT SEAL (to nearest foot)	PUMPING RATE (gal. per min.)
Gray Mica 272 400	from 48 TOP 52 ft. to 54 BOTTOM 58 ft. (enter 0 if from surface) casing CASING RECORD	WATER LEVEL (distance from land surface) BEFORE PUMPING <u>50</u> ft.
Gray Mica 272 400 Opening 410 411 C Gray Mica 411 600	types insert appropriate code below PLL OT OTHER	WHEN PUMPING <u>(COD</u> 22 25 ft. TYPE OF PUMP USED (for test)
Gray M/ca 411 600	MAIN Nominal diameter Iotal depth CASING top (main) casing of main casing TYPE (nearest inch)! (nearest foot)	A air P piston T turbine 27 control other control other C centrifugal R rotary O ther (describe below)
16 m 12 k 1 5 - 2 1 k 1 m 12 k	60 61 63 64 66 70 E OTHER CASING (if used) 4 6 70 A diamater diamater diamater diamater	J jet S submersible
the second is	H inch from to	PUMP INSTALLED PRILLER INSTALLED PUMP (CIRCLE) (YES or NO)
	screen type or open hole ST BR HO	IF DRILLER INSTALLS PUMP, THIS SECTION MUST BE COMPLETED FOR ALL WELLS. TYPE OF PUMP INSTALLED PLACE (A,C,J,P,R,S,T,O) 29 IN BOX 29.
Ent.	insert appropriate code below ENTEL BRASS BRONZE PL DOT OTHER	CAPACITY: GALLONS PER MINUTE (to nearest gallon) 31. 35
	DEPTH (nearest ft.)	PUMP HORSE POWER PUMP COLUMN LENGTH (nearest ft.)
WELL HYDROFRACTURED	E + HO 65 600	CASING HEIGHT (circle appropriate box and enter casing height)
CIRCLE APPROPRIATE LETTER A WELL WAS ABANDONED AND SEALED WHEN THIS WELL WAS COMPLETED E ELECTRIC LOG OBTAINED	H ² 23 24 28 30 32 36 S C 3 R 38 39 41 45 47 51	below LAND SURFACE
P TEST WELL CONVERTED TO PRODUCTION WELL I HEREBY CERTIFY THAT THIS WELL HAS BEEN CONSTRUCTED IN ACCORDANCE WITH COMAR 28.04.04 "WELL CONSTRUCTION" AND IN CONFORMANCE WITH ALL CONDITIONS STATED IN THE ABOVE	E SLOT SIZE 1 2 3 DIAMETER (NEAREST OF SCREEN INCH)	LATITUDE 39. 250825 LONGITUDE 76. 982.246
CAPTIONED PERMIT, AND THAT THE INFORMATION PRESENTED HEREIN IS ACCURATE AND COMPLETE TO THE BEST OF MY KNOWLEDGE.	66 60 from to	(DEFAULT COORD. WGS 84) Pursuant to \$10-624 of the State Govt. Article of the Maryand Code personal info. requested on this form is used in processing this form pursuant
DRILLERS SIGNATURE (MUST MATCH SIGNATURE ON APPLICATION)	IF WELL DRILLED WAS FLOWING WELL INSERT F IN BOX 68 68 68 68 MDE USE ONLY	to COMAR 26.04.04. Failure to provide the info. may result in this form not being processed. You have the right to inspect, amend, or correct this form. The Maryland Department of the
LIC. NO.1 J5D 038,	(NOT TO BE FILLED IN BY DRILLER) T (E.R.O.S.) W Q	Environment is subject to the Maryland Public Information Act. This form may be made available on the Internet via MDE's website and is
SITE SUPERVISOR (sign. of driller or journeyman responsible for sitework if different from permittee)	70 72 TELESCOPE LOG 74 75 76 INDICATOR OTHER DATA COUNTY	subject to inspection or copying, in whole or in part, by the pulic and other governmental agencies, if not protected by federal or state law.