Ci	SEQUENCE NO. (MDE USE ONLY)	STATE OF MARYLAND WELL COMPLETION REPORT	THIS REPORT MUST BE SUBMITTED WITHIN 45 DAYS AFTER WELL IS COMPLETED.
(THIS NUMBER IS TO BE PUNCHED IN COLE. 3+6 ON ALL CARDS)		FILL IN THIS FORM COMPLETELY PLEASE PRINT OR TYPE	COUNTY A 48839
ST/CO USE ONLY DATE Received	DATE WELL COMPL	ETED Depth of Well	PERMIT NO. FROM "PERMIT TO DRILL WELL"
8 13	020290	22 3 4 0 26 (TO NEAREST FOOT) 26	28 29 30 31 32 33 34 35 36 37
OWNERThompson		Dale	28 25 30 31 32 33 34 33 36 37
STREET OR RFD Tast name Quarterfield Definition TOWN W. Friendship SUBDIVISION QUARTER FIELD SECTION LOT 23/			
CROUTING DECORD APS 100			
WELL LOG  Not required for driven wells		WELL HAS BEEN GROUTED (Circle Appropriate Box)	C 3
STATE THE KIND OF FORMATIONS PENETRATED, THEIR COLOR, DEPTH,		TYPE OF GROUTING MATERIAL (Circle one)	PUMPING TEST HOURS PUMPED (nearest hour)
THICKNESS AND IF WATER BEARING		CEMENT C M BENTONITE CLAY B C	8 9
DESCRIPTION (Use additional sheets if needed)	FROM TO if water bearing	NO. OF BAGS 18 NO. OF POUNDS 1692 GALLONS OF WATER 188	PUMPING RATE (gal. per min.)
Sand	0 49	DEPTH OF GROUT SEAL (to nearest foot) from tt. to #/D   ft.	METHOD USED TO MEASURE PUMPING RATE Bucket
	, , , ,	48 TOP 52 54 BOTTOM 58 (enter 0 if from surface)	WATER LEVEL (distance from land surface)
Comming	49 3110	casing CASING RECORD	BEFORE PUMPING 4 17 17 16t.
Sana Gray Mica Rock	1 340 2	(insert appropriate) STEEL CONCRETE	WHEN PUMPING 2/15 ft.
		code below PL OT	TYPE OF PUMP USED (for test)
		PLASTIC OTHER  MAIN Nominal diameter Total depth	A air P piston T turbine
		CASING top (main) casing of main casing TYPE (nearest inch)! (nearest foot)	C centrifugal R rotary O (describe
			27 Delow)
		60 61 63 64 66 70	J jet Submersible
		OTHER CASING (if used) C diameter depth (feet)	PUMP INSTALLED
		inch from to	DRILLER WILL INSTALL PUMP YES NO (CIRCLE) (YES or NO)
		s	IF DRILLER INSTALLS PUMP, THIS SECTION
		screen type SCREEN RECORD	MUST BE COMPLETED FOR ALL WELLS.  TYPE OF PUMP INSTALLED
		or open fiole ST BR HO	PLACE (A,C,J,P,R,S,T,O) IN BOX 29.
·		appropriate STEEL BHASS OPEN BRONZE HOLE	CAPACITY: GALLONS PER MINUTE
NUMBER OF UNSUCCESS	SFUL WELLS: O	below P L OT OTHER	(to nearest gallon) 31 35
WELL HYDROFRACTURE	P Yes N	C 2	PUMP COLUMN LENGTH
CIRCLE APPROPRIATE LETTER		DEPTH (nearest ft.)	(nearest ft.) 43 47
A WELL WAS ABANDONED AND SEALED		\[ \frac{1}{c} \frac{1}{f} \fr	CASING HEIGHT (circle appropriate box and enter casing height)
E ELECTRIC LOG OBTAINED		H s 2	LAND SURFACE
P TEST WELL CONVERTED TO PRODUCTION WELL		C 23 24 26 30 32 36	below ) 3 (nearest) foot)
I HEREBY CERTIFY THAT THIS WELL HAS BEEN CONSTRUCTED IN ACCORDANCE WITH COMAR 26.04.04 "WELL CONSTRUCTION" AND		E 3	A LOCATION OF WELL ON LOT
IN CONFORMANCE WITH ALL CONDITIONS STATED IN THE ABOVE CAPTIONED PERMIT, AND THAT THE INFORMATION PRESENTED HEREIN IS ACCURATE AND COMPLETE TO THE BEST OF MY		SLOT SIZE 1 2 3	SHOW PERMANENT STRUCTURE SUCH AS BUILDING, SEPTIC TANKS, AND /OR
KNOWLEDGE.		DIAMETER (NEAREST INCH)	LANDMARKS AND INDICATE NOT LESS THAN TWO DISTANCES
TYPE: MWD/MSD/MGD DRILLERS LIC. NO.		from to	(MEASUREMENTS TO WELL)
George & . Mayne		GRAVEL PACK	2
DRILLERS SIGNATURE "		FLOWING WELL INSERT F IN BOX 68 68	iau
(MUST MATCH SIGNATURE ON APPLICATION)		MDE USE ONLY (NOT TO BE FILLED IN BY DRILLER)	4 30 8
LIC. NO. 3		T (E.R.O.S.) W Q	E 12 Je 20
SITE SUPERVISOR (sign of driller or journeyman		70 72	6 1.
responsible for sitework if different from permittee)  TELESCOPE LOG OTHER DATA  CASING INDICATOR			
COUNTY			

