c1 3432	SEQUENCE NO. (MDE USE ONLY)	STATE OF MARYLAND WELL COMPLETION REPORT	THIS REPORT MUST BE SUBMITTED WITHIN 45 DAYS AFTER WELL IS COMPLETED.
1 2 3 6 (THIS NUMBER IS TO BE PUNCHED IN COLS. 3-6 ON ALL CARDS)		FILL IN THIS FORM COMPLETELY PLEASE TYPE	COUNTY NUMBER
ST/CO USE ONLY DATE Received	DATE WELL COMPL	22 480 26	OF PERMIT NO. OF FROM "PERMIT TO DRILL WELL" 15/16 Sc 28 29 30 31 32 33 34 35 36 37
OWNER MATCH STREET OR RED 36 HT BIVE HILL COUT MIX NAME TOWN EMICHT City			
SUBDIVISION Gray Rock SECTION LOT 2			
WELL LOG Not required for driven wells		GROUTING RECORD	
STATE THE KIND OF FORMATIONS PENETRATED, THEIR COLOR, DEPTH, THICKNESS AND IF WATER BEARING		TYPE OF GROUTING MATERIAL (Circle one)	PUMPING TEST HOURS PUMPED (nearest hour)
DESCRIPTION (Use additional sheets if needed) FRO	FEET check if water bearing	CEMENT CM BENTONITE CLAY BC NO. OF BAGS 46 NO. OF POUNDS 45 46	8 9
Dift 0	80	GALLONS OF WATER DEPTH OF GROUT SEAL (to nearest foot)	PUMPING RATE (gal. per min.)
Hard gray 80	84	from ft. to ft. to ft.	WATER LEVEL (distance from land surface)
Soft Brown 8	185	(enter 0 if from surface) casing CASING RECORD	BEFORE PUMPING 17 20 ft.
Havdgray 85	-89	types insert appropriate	WHEN PUMPING 22 25 ft.
Gaft Brown 8	190	below PLASTIC OT	TYPE OF PUMP USED (for test)
Have gray 90	97	MAIN Nominal diameter Total depth CASING top (main) casing of main casing TYPE (nearest inch)! (nearest foot)	A air P piston T turbine
Coff Broken 97	198	ST 6 72	C centrifugal R rotary O (describe below)
Hardgray 92	8107	60 61 63 64 66 70 E OTHER CASING (if used) diameter depth (feet)	J jet S submersible
Kapt Broken 107	110	G ST inch from to 8	PUMP INSTALLED DRILLER INSTALLED PUMP YES NO
Hard gray 116	114		(CIRCLE) (YES or NO) IF DRILLER INSTALLS PUMP, THIS SECTION
Soft Broken 114	115	screen type SCREEN RECORD	MUST BE COMPLETED FOR ALL WELLS. TYPE OF PUMP INSTALLED
Hard green 115	- 480	or open hole ST BR HO insert STEEL BRASS OPEN	PLACE (A,C,J,P,R,S,T,O) 29 IN BOX 29. CAPACITY :
		(appropriate code below BRONZE HOLE PL OT	GALLONS PER MINUTE (to nearest gallon) 31 35
		C 2 DEPTH (nearest ft.)	PUMP HORSE POWER 37 41
NUMBER OF UNSUCCESSFUL WELLS:			(nearest ft.) 43 47
WELL HYDROFRACTURED	YN	A 9 11 15 17 21 C 2	+ above) and enter casing height)
CIRCLE APPROPRIATE LETTER A WELL WAS ABANDONED AND SEALED WHEN THIS WELL WAS COMPLETED		H 23 24 26 30 32 36 S C 3	49 LAND SURFACE (nearest) foot)
E ELECTRIC LOG OBTAINED P TEST WELL CONVERTED TO PRODUCTION WELL		R 38 39 41 45 47 51 E E SLOT SIZE 1 2 3	49 50 51 1000
I HEREBY CERTIFY THAT THIS WELL HAS BEEN CONSTRUCTED IN ACCORDANCE WITH COMAR 26.04.04 "WELL CONSTRUCTION" AND IN CONFORMANCE WITH ALL CONDITIONS STATED IN THE ABOVE CAPTIONED PERMIT, AND THAT THE INFORMATION PRESENTED HEREIN IS ACCURATE AND COMPLETE TO THE BEST OF MY		N DIAMETER OF SCREEN 56 60 (NEAREST INCH)	SHOW PERMANENT STRUCTURE SUCH AS BUILDING, SEPTIC TANKS, AND /OR LANDMARKS AND INDICATE NOT LESS THAN TWO DISTANCES
DRILLERS LIC. NO. 1 MW D3 0 4		GRAVEL PACK	(MEASUREMENTS TO WELL)
DRILLERS SIGNATURE		IF WELL DRILLED WAS FLOWING WELL INSERT F IN BOX 68 68	1510e Hill A1.32
		MDE USE ONLY (NOT TO BE FILLED IN BY DRILLER) T (E.R.O.S.) W Q	2 x 81.36
Jason Morrison		70 72	1× 00,110
SITE SUPERVISOR (sign. of driller or journeyman responsible for sitework if different from permittee)		TELESCOPE LOG 74 75 76 CASING INDICATOR OTHER DATA	House 66148

COUNTY