PERMIT

SEWAGE DISPOSAL SYSTEM

DEPARTMENT OF HEALTH AND MENTAL HYGIENE

P 47115

A REPAIR

DISTRICT

DATE_

RH

HOWARD COUNTY HEALTH DEPARTMENT

BUREAU OF ENVIRONMENTAL HEALTH

461-9933

INDEXED

			INSPECTOR
	Jack Fyock Septic Service	IS PERMITTED TO I	NSTALLALTER X
ADDRESS 13775 Tria	adelphia Road, Glenelg, Maryland	21737 PHONE_	988-9270
SUBDIVISION	LOT	ROAD <u>14120 Tri</u>	adelphia Road
PROPERTY OWNER	Torklidsen		
ADDRESS			
SEPTIC TANK CAPACITY _	GALLONS		1
NUMBER OF BEDROOMS_	<u>a 3</u>	· ·	
125 SQUARE FEI	ET PER BEDROOM		()
LINEAR FEET OF TRENCH			
REPAIR - DRYWELL	IS FULL. CALL FOR INSPECTION WHE	N GROUND IS OPENED	SO SANITARIAN CAN
DECOMMENT		A CONTRACTOR OF THE CONTRACTOR	ELL
BUNN	ING TO WARD	BACK	
TREALH	70 BB 68F7 4	ONG ZRY	WIDE
101/2 ET	NEED WITH INLE		NGCP
51/2 = 7	OFSTONE		,
PLANS APROVED BY	Craig William	ns cm	DATE05/03/91
COVER NO WORK UNTIL INSP	ECTED AND APPROVED		
NEITHER THE HOWARD COUN	ITY COUNCIL NOR THE HEALTH DEPARTMENT IS RESPON	ISIBLE FOR THE SUCCESSFUL OF	PERATION OF ANY SYSTEM
NOTE: CLEANOUT REQUIRED ACCEPTABLE.	D EVERY 70 FEET OF SEWER LINE AND/OR AT 90° SI	WEEPS IN LINES FROM HOUSE	TO DRAIN FIELDS, 90° ELBOWS NOT
NOTE: ALL PARTS OF SEPT AUTHORIZED)	TIC SYSTEMS (I.E. TANK, DISTRIBUTION BOX TRENCHES	S) TO BE 100 FEET FROM WELL	L (UNLESS OTHERWISE SPECIFICALLY
NOTE: IF DEEP TRENCH(ES)	ARE USED CALL FOR INSPECTION BEFORE AND AFTER P	LACING GRAVEL IN TRENCH(ES)	••
NOTE: NO DRY WELL SHALL	EXCEED 15 FOOT IN DIAMETER NO ABSORPTION TRENCH	I TO EXCEED 100 FEET IN LENGT	н
NOTE: ALL PIPE FROM HOUS	E TO SEPTIC TANK MUST BE CAST IRON OR SCHEDULE 3	5/40 PVC OR ABS	
PERMIT VOID AFTER TWO YEA			
NOTE: INSTALL STAND PIPE PVA OR ABS ACCEPTE	ON SEPTIC TANK AND DRY WELL STAND PIPES MUST B ED. IF TOP OF SEPTIC TANK IS DEEPER THAN 3 FEET. MAR	E 6 INCHES IN DIAMETER CAST I NHOLE TO GRADE REQUIRED.	RON. CONCRETE OR TERRA COTTA OF

NOTE: DISTRIBUTION BOXES MUST HAVE BAFFLES

	50	100	50- 60-20	0 25	50
O REO CLAY			÷		
BROWT 200 SAND NOAN		75 ->(3)		SID A	200
150	SQ1/S	6 × m			150
100	6	HOUSE	1		100
. 50					50
	¥ . v	RIPS L P'H	ROADWAY AS BAS	ELINE	
SEPTIC TANK LEVEL		CLEANG	OUTS		211
DISTRIBUTION BOX I	. ,				3790
	DEPTH <u>5 /2</u> FT.	TRENCH WIDTH		INLET DEPTH	<u> </u>
	DEPTH 10//LFT.		•	374 so F	т
	AMETERFT.	EFFECTIVE DEPTH			
ABSORB	ENT AREA SQ.	FT. <i>Cropp</i> . T	APAICH	1006	
* ADD A	REMAINDE - RIF	R OF ST	ONE T	O TIPP	ENCH
·					
	á				
DATE SYSTEM APPR	ROVED 3/7/7	INSPE	CTOR Ray	monel	frego